

RIN Endless Design - Glass Door Reach In Refrigerators with 24" Wide Doors

• PRODUCT SPECIFICATIONS SHEETS



- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Remote	RIN2-24	RIN3-24	RIN4-24	RIN5-24
Length with ends	54-7/8"	78-7/8"	102-3/8"	126-1/8"
Height	78-1/2"	78-1/2"	78-1/2"	78-1/2"
Depth with ends	35-1/2"	35-1/2"	35-1/2"	35-1/2"
(Dimensions are +/-1/4")				

- Specification subject to change without notice

RIN Endless Design - Glass Door Reach In Refrigerators with 24" Wide Doors

Standard Specifications and Optional Features

<p>CONSTRUCTION UL Classified to ANSI/NSF 7 Heavy duty construction CFC free foamed in place insulation 2, 3, 4, or 5 door models available Inset door assembly Endless for continuous line ups</p>	<p>FINISHES Frame assembly and door - Anthony style 101 Exterior-designer white Interior-designer white</p>
<p>INTERIOR White ends Back is a combination of <i>white and perforated aluminum</i> Removable floor racks 5 heavy duty white epoxy shelves per door</p>	<p>REFRIGERATION Remote with R22 expansion valve Coil and fans located below floor pans</p>
<p>EXTERIOR White aluminum ends and fronts Double pane glass doors 24"X63" Black kick plate</p>	<p>LIGHTING 60" fluorescent lamps 2 Dr = 3 lights 3 Dr = 4 lights 4 Dr = 5 lights 5 Dr = 6 lights</p>
<p>ELECTRICAL REQUIREMENTS Fans and lighting - 115V/60Hz/1Ph Unit must be hard wired UL/CUL listed</p>	<p><i>Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.</i></p> <p><i>Important Note: Product must be cooled before being displayed within the case.</i></p>

OPTIONAL FEATURES

<p>Stainless steel, laminate or paint Digital thermometer Door swing change Insulated divider Plexiglas divider</p>	<p>Door locks Special door frames Temperature control thermostat Joint kit</p>
---	---



RIN Endless Design - Glass Door Reach In Refrigerators with 24" Wide Doors

Technical Data

Model	Remote	RIN2-24	RIN3-24	RIN4-24	RIN5-24
Length Height Depth (Dimensions are +/- 1/4")		54-7/8" 78-1/2" 35-1/2"	78-7/8" 78-1/2" 35-1/2"	102-3/8" 78-1/2" 35-1/2"	126-1/8" 78-1/2" 35-1/2"
Operating temperature Refrigerant (expansion valve) BTU's at +20°F Evap. Temp. Voltage Amperage Cord and plug		36°F to 40°F R22 2473 115V 4.4A No	36°F to 40°F R22 3471 115V 6.2A No	36°F to 40°F R22 4481 115V 8.0A No	36°F to 40°F R22 5522 115V 9.9A No
Exterior color Interior color Inside end panels Floor-removable deck pans Drain required Total shelves Door size		White White White White Yes 10 24"X63"	White White White White Yes 15 24"X63"	White White White White Yes 20 24"X63"	White White White White Yes 25 24"X63"

SHIPPING INFORMATION

Height		83"	83"	83"	83"
Length		61"	86"	107"	134"
Depth		43"	43"	43"	43"
Gross weight		568#	832#	1096#	1360#
Cubic feet		125ft ³	177ft ³	221ft ³	276ft ³

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Specification subject to change without notice

RIN Endless Design - Glass Door Reach In Refrigerators with 24" Wide Doors

Technical Data • Side View • Plan View

