

SC-OD35E-33L-B-LED - MOBILE MERCHANDISER



MODEL NO.	DESCRIPTION	LENGTH	DEPTH	HEIGHT	VOLTAGE	AMPS	НР	CORD	WEIGHT
SC-OD35E-33L-B-LED	Self Contained	33.75"	34.5"	60"	115	14.0	1/2	5-20P	700

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

Prefix	Suffix			
SC = Self Contained	B = Black			
R = Remote	W = White			

S = Stainless Steel LED = LED lighting Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
 Cases are equipped with drains; check your local building codes for

connection requirements.

• Specification subject to change without notice















STANDARD SPECIFICATIONS AND OPTIONAL FEATURES

CONSTRUCTION

- UL Classified to ANSI/NSF 7
- · Foamed in place CFC free foam
- · Heavy gauge steel super structure

INTERIOR

- Black end panels
- Removable black floor pans
- Black perforated rear wall (for even air distribution)
- Full length lighting at top of unit

EXTERIOR

- · Black ends and front
- Removeable front grill allows for cleaning and servicing

FINISHES

- · Black end panels
- · Black front rail
- Black end trim

LIGHTING

• 2 strips of LED lighting inside top of unit

ELECTRICAL REQUIREMENTS

- · Cord and Plug
- Receptacle on back (separate circuit)

REFRIGERATION

- Low velocity fans located below deck area (to insure even flow of air)
- Electronic Control System with automatic air defrost to maintain balanced temperatures
- · New high efficency air screen technology
- Self contained system
- Hermetic unit
- Built-in condensate system included

OPTION

Night Cover

IMPORTANT NOTE:

ALL REFRIGERATED CASES ARE DESIGNED TO OPERATE IN AN ENVIRONMENT OF 75 DEGREES AND 55% RELATIVE HUMIDITY.

PRODUCT MUST BE COOLED BEFORE BEING DISPLAYED WITHIN THE CASE. DRAIN IS REQUIRED



SC-OD35E-33L-B-LED - MOBILE MERCHANDISER

TECHNICAL DATA

Model No.	sc	SC-OD35E-33L-B-LED		
Length with (2) ends		33.75"		
Length without ends		30.75"		
Height with ends		60.00"		
Height with casters		61.00"		
Depth with ends		34.50"		
Depth without ends		34.50"		
Endless design (Dimensions are +/- 1/4")		YES		
Operating temperature		38°F to 41°F		
Compressor size HP		1/2		
Defrost per day (24 hours)	Air Defrost	6		
Voltage	SC	115		
Amperage	SC	14.0		
Cord and plug	SC	5-20P		
Exterior color		Black		
Interior color		Black		
# of shelves		2 Shelves		
Size of shelves	ı	12.00", 14.00"		

<sup>Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
Cases are equipped with drains; check your local building codes for connection requirements.</sup>

[•] Specification subject to change without notice



SC-OD35E-33L-B-LED MOBILE MERCHANDISER

DRAWINGS • SIDE VIEW • FRONT VIEW • PLAN VIEW

