





Remote							HP/	Power	Est. Ship
Model No.	Description	Length	Depth	Height	Voltage	Amps	BTUs	Cord	Weight
SC-OM35E-4L-LB-B	Self Contained	51.00"	34.50"	74.00"	115/208-230	13.0	1/2	L14-20P	965
R-OM35E-4L-LB-B	Remote	51.00"	34.50"	60.00"	115	3.0	4733	No	585

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

Prefix	Suffix		
SC = Self Contained	B = Black		
R = Remote	W = White		

S = Stainless Steel LED = LED lighting • Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

· Cases are equipped with drains; check your local building codes for connection requirements.

Specification subject to change without notice









Howard McCray • 831 East Cayuga St • Philadelphia, PA 19124 USA • (215) 464-6800 1-800-344-8222 • Fax (215) 969-4890 • E-Mail: sales@howardmccray.com • www.howardmccray.com



Standard Specifications and Optional Features

CONSTRUCTION

- UL Classified to ANSI/NSF 7
- · Foamed in place CFC free foam
- Heavy gauge steel super structure
- Multi deck
- Endless design allows for continuous line up (Remote Only)

INTERIOR

- Black
- Removable black floor pans
- Black perforated rear wall (for even air distribution)
- · Full length lighting at top of unit
- 3 levels of lighted shelving
- · 4 levels of product display
- · Price tag molding on each shelf

EXTERIOR

- · Black ends, front and rear
- Removeable front grill allows for cleaning and servicing
- 1" bumper
- 4" Curved plexi end panels

LIGHTING

- 1 row at inside top of unit
- 3 rows of lighted shelving

ELECTRICAL REQUIREMENTS

- Self contained unit comes with cord and plug
- UL/CUL listed
- · See Tech page for details on voltage

REFRIGERATION

- · Self contained expansion valve system
- Low velocity fans located below deck area (to insure even flow of air)
- Electronic control system with automatic air defrost to maintain balanced temperatures (SC)
- New high efficiency air screen technology

OPTIONAL FEATURES

- Wide view plexi end panels
- Night covers
- Digital thermometer
- Condensate pan and pump kit



Technical Data

Model No.		SC-OM35E-4L-LB-B	R-OM35E-4L-LB-B
Length with (2) ends		51"	51"
Length without ends		48"	48"
Height with ends		74"	60"
Depth with ends		34.5"	34.5"
Depth without ends		34"	34"
Endless design (Dimensions are +/- 1/4")		NO	YES
Operating temperature		36°F to 40°F	36°F to 40°F
Refrigerant (exp. valve)			
Defrost per day (24 hours)	Air Defrost	6 per day	6 per day
BTU's at +20°F Evap. Temp.		N/A	4733
Remote Voltage		115	115
Amperage	SC	13.0	
Amperage, lights only	R	N/A	3.0
Cord and plug	SC	Nema L14-20P	No
Exterior color		BLACK	BLACK
Interior color		BLACK	BLACK
# of rows / shelves		3	3
Shelf Size		(1) 16", (2) 18"	(1) 16", (2) 18"
Shipping Info Height		86"	68"
Depth		44"	44"
Length		61"	61"
Gross weight		965	585
Cubic feet		134	106

[•] Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

[•] Cases are equipped with drains; check your local building codes for connection requirements.

Specification subject to change without notice



DRAWINGS • SIDE VIEW • PLAN VIEW

